



SPECIFICATIONS:

- CAPACITY: (2) 20' CONTAINERS OR (1) 40' CONTAINER
- GENERAL DIMENSIONS: 40' LENGTH, 96" OVER BLOSTERS (102" OVER TIRES)
- STRUCTURE: PICK UP PLATE 5-16" REINFORCED WITH 1/4" FORMED CHANNELS, FABRICATED SQUARE TUBING 7 x 7" 3/8" TOP PLATE 1/4" SIDES AND BOTTOM WITH 1/4" STIFFENERS
- CROSSMEMBERS: 7-GAUGE STEEL
- LATCHING SYSTEM: ISO STANDARD TWIST LOCKS
- AXLES: (3) 30,000LBS AMPRO® TRI-AXLES
- SUSPENSION: 84,000LBS 3 LEAF SPRING SUSPENSION
- LANDING GEAR: STANDARD, 10" BY 10" LOW PROFILE SANDSHOE
- TIRES: 295/75R22.5
- WHEELS: 22.5x8.25, 10 HOLE DISC, HUB-PILOTED, UNI-MOUNT
- BRAKES: AIR, 16, 5" x 7" x 3/4" ACP®
- HALDEX® ABS BRAKES ON BOTH AXLES, SENCES FROM REAR AXLE
- LED STOP/MARKER LIGHTS
- POWDER COAT PAINT

